TECHNICAL CHARACTERISTICS

TUTELA TRANSMISSION FE-GEAR

PRODUCT CODE: 2313

APPLICATION

Synthetic lubricant for manual and automated gearboxes with standard or carbon synchronizers; fuel economy characteristics; for heavy duty commercial vehicles with or without Intarder; oil drain interval up to 360.000 Km.

SPECIFICATIONS

SAE 75W-80, API GL 4, IVECO 18-1807 CLASS MGS1,CONTRACTUAL TECHNICAL REF. N°I112.F11, ZF TE-ML 01L,02L,16K, MAN 341 Type E3, MAN 341 Type Z4

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	BRIGHT
DENSITY AT 15°C	ASTM D4052	g/cm³	0,860
VISCOSITY AT 100°C	ASTM D445	cSt	9,65
VISCOSITY INDEX	ASTM D2270	--	153
VISCOSITY AT -40°C	ASTM D2983	cPs	95000
FLASH POINT Cl. O. C.	ASTM D92	°C	230
POUR POINT	ASTM D97	°C	-42

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT 04/2015